

Dialog Widget Class

[Github Link](#)

```
namespace lc::ui::api
```

A Dialog widget object acts a parent widget containing all the input gui widgets. A finish button can be added which on being clicked retrieves the values of all the input guis in a table when the user is finished with the dialog.

Constructor

Description

Constructs a dialog widget object. This dialog widget contains all the input gui widgets. The constructor takes in a label and a mainwindow pointer as parameters. Can be constructed using the

```
CreateDialogWidget("DialogLabel")
```

which takes care of passing in the mainwindow as parameter.

- Dialog Label - *string* , Current MainWindow - *MainWindow*

Examples

```
local dialog1 = gui.DialogWidget("Dialog1", mainWindow)
```

```
local dialog1 = CreateDialogWidget("Dialog1")
```

Add Input GUI Widget

Description

Add an input gui widget to the dialog widget. Expects a key and input widget as parameters. Key is used to retrieve the value of the input gui widget.

Note:- If button or checkbox is added, the addWidget function first adds it to a horizontal group gui widget which is then added to the dialog widget.

- Key - *string* , Input GUI Widget - *InputGUI*

Examples

- ```
local angle1 = gui.AngleGUI("AngleWidget")
dialog1:addWidget("angle1", angle1)
```

---

## Get list of input widgets

### Description

Returns a list of all input widgets present in the dialog widget.

### Examples

- ```
local guiwidgets = dialog1:inputWidgets()
```

Title

Description

Get and set title for the dialog widget

Examples

- ```
message(dialog1:title())
```
- ```
dialog1:setTitle("New Dialog")
```

Set Finish Button

Description

Set a button as the finish button for the dialog widget which on being clicked will return a table of all values to all the finish lua callbacks added to the dialog widget.

- Finish button - *ButtonGUI*

Examples

- `dialog1:setFinishButton(button1)`
-

Add Finish Callback

Description

Add a finish callback which is called whenever the user is done with the dialog and clicks on the finish button. The callback is passed in a table containing the key and value of all the input gui widgets.

- Lua Callback - *kaguya::LuaRef*

Examples

- `dialog1:addFinishCallback(function(valTable) for k,v in pairs(valTable) do message(tostring(k) .. tostring(v)) end end)`
-

Get keys

Description

Last update:

2020/07/09 dev:v3:gui_api:dialog:dialogwidget https://dokuwiki.librecad.org/doku.php/dev:v3:gui_api:dialog:dialogwidget?rev=1594269974
04:46

Returns a list of keys of all the input gui widgets in the dialog.

Examples

- `local keyList = dialog1:keys()`
-

From:

<https://dokuwiki.librecad.org/> - Wiki

Permanent link:

https://dokuwiki.librecad.org/doku.php/dev:v3:gui_api:dialog:dialogwidget?rev=1594269974

Last update: **2020/07/09 04:46**

